

Factory glazed frame constructed from extruded aluminium profile, thermally broken with polyamide insulation sections. Supplied as standard polyester powder coated to dual colour finish. RAL 9010 (White) to internal section and RAL 9005 (Black) to external section.

Extruded aluminium 'clip-on' capping profile, supplied as standard polyester powder coated to RAL 7015 (Slate Grey).

26mm Insulating glass unit, comprising of:
 4mm Clear toughened outer pane, 16mm Argon filled cavity (Silicone Sealed), 6mm Clear toughened super low-E coated inner pane. (Centre pane U-value 1.2 W/m²K)

Plasterboard engages with framework at unique Decorstop detail, minimising internal sight lines.

8mm bead of neutral curing silicone sealant to perimeter of upstand applied prior to fitting of skylight.


Fully insulated upstand supplied by Sunsquare Limited. Constructed from 2No. WBP (marine grade) plywood, 32mm polyfoam rigid insulation and european whitewood (treated) capping.

12.7 Plasterboard and Skim (By Others)

Overall Aero Dimensions Taken From Internal Structural Opening

Section Through Upstand/Framework Construction

Sunsquare Ltd
 5A Barton Road Trading Estate
 Bury St Edmunds
 Suffolk
 IP32 7BE
 T. 0845 226 3172 .F. 0845 226 3173
 info@sunsquare.co.uk; www.sunsquare.co.uk



Product:	Aero (Standard Glazing)	Scale:	1:2.5 @ A3	Drawing No.:	AERO-STD-001
Description:	Section Through Upstand / Framework Construction	Date:	May 2011	Drawn By:	AC
By:		Date:		Revision:	