

Factory glazed frame constructed from extruded aluminium profile, thermally broken with polyamide insulation sections. Supplied as standard polyester powder coated to dual colour finish. RAL 9010 (White) to internal section and RAL 9005 (Black) to external section.


Extruded aluminium 'clip-on' capping profile, supplied as standard polyester powder coated to RAL 7015 (Slate Grey).

47.5mm Insulating glass unit, comprising of: 25.5mm Clear toughened/Laminated (Heat Soaked) outer pane, 16mm Argon filled cavity (Silicone Sealed), 6mm Clear toughened super low-E coated inner pane, (Centre pane U-value 1.1 W/m²K)

Dashed line denotes internal edge of upstand

OVERALL HORIZON DIMENSIONS TAKEN FROM INTERNAL STRUCTURAL OPENING

OVERALL HORIZON DIMENSIONS TAKEN FROM INTERNAL STRUCTURAL OPENING

<b>Sunsquare Ltd</b> 5A Barton Road Trading Estate Bury St Edmunds Suffolk IP32 7BE T. 0845 226 3172 .F. 0845 226 3173 info@sunsquare.co.uk; www.sunsquare.co.uk			
Rev:	Description:	By:	Date:
Product: Horizon Description: Plan Elevation of Wall Abutting Horizon (Abutting on Three Edges)		Scale: 1:5 @ A3 Date: May 2011 Drawn By: AC	Drawing No.: HORIZON-STD-004 Revision: